

DS-3E0524-E(B)

24 Port Gigabit Unmanaged Switch



- 24 x Gigabit Ethernet port
- Supports IEEE 802.3, IEEE 802.3u and IEEE 802.3x
- Gigabit network access
- Wire-speed forwarding and non-blocking design
- Store-and-forward switching
- Solid high-strength metal shell
- Fan-free design with high reliability

▪ Specification

Model		DS-3E0524-E(B)
General	Shell	Metal material, fan-free design
	Net Weight	1.60 kg (3.50 lb)
	Gross Weight	2.47 kg (5.44 lb)
	Dimensions (W × H × D)	335.0 mm × 44.5 mm × 175.8 mm (13.2" × 1.8" × 6.9")
	Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Storage Temperature	−40°C to 85°C (−40°F to 185°F)
	Operating Humidity	5% to 95% (no condensation)
	Relative Humidity	5% to 95% (no condensation)
	Power Supply	220 V AC, 50/60 Hz, Max. 0.7 A
	Installation Mode	Metal material, fan-free design
	Surge Protection	6 kV
	Ports	24 × Gigabit RJ45 port
Network Parameters	MAC Address Table	8 K
	Switching Capacity	48 Gbps
	Packet Forwarding Rate	35.72 Mpps
	Internal Cache	4.10 Mbits
	EMC	FCC (47 CFR Part 15, Subpart B),CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue 7:2020),RCM (AS/NZS CISPR 32: 2015)
Approval	Safety	UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
	Chemistry	CE-RoHS (2011/65/EU),WEEE (2012/19/EU),Reach (Regulation (EC) No.1907/2006)

▪ Available Model

DS-3E0524-E(B)

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global

Hikvision
Corporate Channel

Hikvisionhq