

# Catalogue

# 2025



[www.micruxfluidic.com](http://www.micruxfluidic.com)

THINK & INNOVATE

*Smart Microfluidic and Electrochemical Solutions for Research Science*

*Last update: April 2025*

# distribuidora oficial

 **SCQ**  
SOLUÇÕES LABORATORIAIS

 **micrux**  
TECHNOLOGIES

A SCQ possui uma linha de produtos completa para cientistas e pesquisadores que buscam qualidade, facilidade e rapidez.

Localizada em São Carlos/SP - a capital da tecnologia - contamos com ampla cobertura comercial, atendendo toda a América Latina.



**+31** anos  
impulsionando  
a ciência



**+9.500**  
clientes atendidos



**+25**  
empresas parceiras




**+40.000**  
unidades em estoque

## áreas de atuação

Indústria  
Universidade  
Laboratórios Químicos  
Laboratórios de Análises  
Controle de Qualidade  
Engenharia de Materiais  
Engenharia Química  
Eletroquímica  
Análise de Água e Ar  
Farmácia  
Petroquímica

Biotecnologia  
Genética  
Agronegócio  
Química  
Biofarma  
Biologia  
Microbiologia  
Botânica  
Saúde  
Veterinário  
Patologia



## » Presentation

**MicruX Technologies** is an innovative technology-based company expertise in electrochemistry and microfluidic platforms, founded in 2008 and based in Gijón (Asturias), SPAIN.

**MicruX** develops miniaturized, automated and portable analysis systems. Thus, **Lab-on-a-Chip** (LOC) technologies based on **microfluidics** and **electrochemical sensors** give rise to the integration of multiple steps carried out in a laboratory (sample pretreatment, mixing, reaction, separation, and detection) on a single device. These **miniaturized devices** enable the separation, detection, identification and quantification of compounds with analytical interest in real samples. Thus, these novel devices can be used at **research** and **industrial level** for developing innovative solutions in food, environment and health sector.



**MicruX** is proficient in **microfluidics** and **electrochemical** detection systems especially designed for research and educational activities. In microfluidic field, **MicruX** has extensive experience in developing, manufacturing and application of different **microfluidic devices**. Moreover, our know-how in the electrochemistry field, allow us the design and integration of miniaturized **electrochemical sensors** on a simple and cost-effective way.

**MicruX** also provides a new generation of **analytical instrumentation** in order to make easier the use of the microfluidic and electrochemical devices. Moreover, **MicruX** has the know-how to provide **services** for achieving food, environmental and clinical applications using these novel **microfluidic** and **electrochemical devices**.

**MicruX** contributes to make the use of **microfluidic** and **electrochemical** devices more routinary in different research fields as well as in industry.





# CONTENTS

## 1. ELECTROCHEMICAL & MICROFLUIDIC SOLUTIONS

<b>1.1. THICK-FILM ELECTRODES.....</b>	<b>8</b>
1.1.1. Thick-film single-electrodes (S1PE).....	9
1.1.2. Thick-film mediated single-electrodes (S1PE) .....	15
1.1.3. Thick-film dual-electrodes (D2PE) .....	17
<b>1.2. THIN-FILM ELECTRODES .....</b>	<b>19</b>
1.2.1. Thin-film single-electrodes (SE) .....	20
1.2.2. Thin-film microelectrode arrays (MEA) .....	22
1.2.3. Thin-film interdigitated electrodes (IDE) .....	23
1.2.4. Thin-film interdigitated microelectrode array (IDA) .....	25
1.2.5. Thin-film interdigitated ring array (IDRA) .....	27
1.2.6. On-demand thin-film electrochemical sensors .....	28
<b>1.3. MANUFACTURING SERVICES.....</b>	<b>32</b>
1.3.1. Thin-film electrodes manufacturing services .....	33
1.3.2. Printed electrodes manufacturing services .....	34
1.3.3. Microfluidic manufacturing services.....	35
<b>1.4. ELECTROCHEMICAL &amp; MICROFLUIDIC PLATFORMS.....</b>	<b>36</b>
1.4.1. Drop-cell interface .....	36
1.4.2. All-in-One Platform for thin-film electrodes .....	37
1.4.3. All-in-One SPE Platform for thick-film electrodes.....	39
1.4.4. Multi8x All-in-One Platform.....	40
1.4.5. Multi-electrode Chip Platform.....	42
1.4.6. Other interfaces .....	43
1.4.7. External Electrodes Platform.....	45
<b>1.5. INSTRUMENTATION.....</b>	<b>47</b>
1.5.1. Miniaturized Electrochemical Workstation .....	47
1.5.2. Ultra-compact Electrochemical Sensing Interface.....	50

## 2. ACCESSORIES FOR MICROFLUIDICS & ELECTROCHEMISTRY

<b>2.1. PUMPING SYSTEMS .....</b>	<b>54</b>
2.1.1. Multi-channel LP Peristaltic Tube Pump .....	54
2.1.2. Single & Dual Syringe Pumps LP series .....	56
2.1.3. Single & Multi Syringe Pumps NE series.....	58
2.1.4. Microfluidic & High-pressure Syringe Pumps NE series.....	59
<b>2.2. FLOW SYSTEM PACKS.....</b>	<b>60</b>
2.2.1. Basic fitting pack.....	60
2.2.2. Basic-Plus pack .....	60
2.2.3. Full system pack.....	61
<b>2.3. DIGITAL MICROSCOPE.....</b>	<b>62</b>
<b>2.4. OTHER ACCESSORIES.....</b>	<b>63</b>





## 1. ELECTROCHEMICAL & MICROFLUIDIC SOLUTIONS

---



MicruX develops a wide range of standard and customized **thick- & thin-film electrodes, microfluidic devices** as well as related user-friendly **accessories** and **instrumentation**. Electrochemical sensors provide a cost-effective and useful tool for electroanalytical applications, including the development of (bio)sensors.

## 1.1. THICK-FILM ELECTRODES

MicruX develops **thick-film electrodes** fabricated by printing technologies on flexible and high-resist PET as well as rigid ceramic substrates. These low-cost and disposable electrochemical sensors enable the use of small sample volume.

### » Thick-film electrodes main features



» <b>Standard dimensions:</b>	27.5 x 10.1 mm
» <b>Substrate:</b>	PET (white) / Ceramic ( $\text{Al}_2\text{O}_3$ )
» <b>Substrate thickness:</b>	250 $\mu\text{m}$ / 380 $\mu\text{m}$
» <b>WE area range:</b>	2,3 - 7,1 $\text{mm}^2$
» <b>Sample volume:</b>	20 – 50 $\mu\text{L}$
» <b>Electrode material:</b>	
<b>Working electrodes (WE1 / WE2):</b>	Carbon / Graphene / Gold / Platinum / Carbon-Mediated
<b>Reference electrode (RE):</b>	Silver or Silver/Silver Chloride
<b>Auxiliary electrode (AE):</b>	Carbon / Graphene / Gold / Platinum

Printed electrodes are a suitable tool for **multiple applications**, providing many advantages such as low-cost, disposable, low reagent consumption as well as non-tedious pre-cleaning procedures.

Electroanalysis	Nanotechnology	Biosensors	Flow Analysis Systems
✓ Study EC reactions	✓ Modified electrodes	✓ EC transducers	✓ FIA Systems
✓ Trace EC Analysis	✓ New nanostructures	✓ New recognition elements	✓ Capillary Electrophoresis
✓ In-vivo measurements	✓ New nanomaterials	✓ POC systems	✓ HPLC


Printed-based electrodes are very useful in order to avoid tedious polishing of traditional solid electrodes, and make easier the development of **chemical-sensors** and **bio-sensors** for field analysis.

### 1.1.1. Thick-film single-electrodes (S1PE)


#### » Thick-film carbon single-electrodes

**Carbon** (*Ref. ED-S1PE-C*) thick-film electrochemical sensors are based on a classical three-electrodes (working – WE, reference – RE and auxiliary – AE) approach.

#### » Electrochemical S1PE carbon sensor design



#### » Electrochemical cell




Thick-film carbon-based electrodes are available with different carbon compositions, adapted to the requirements of several applications.

The **high-performance (HP) carbon-based** screen-printed electrodes (*Ref. ED-S1PE-C1XX*) with an excellent intra- and inter electrode precision are the suitable option for the development of chemical sensors and biosensors.


The **low-cost (LC) carbon-based** screen-printed electrodes (*Ref. ED-S1PE-C2XX*) are the best option for basic electrochemical studies. These electrodes show an excellent electrochemical performance with good reversibility when using cyclic voltammetry.

## » Thick-film carbon single-electrodes performance


Thick-film carbon-based electrodes show an excellent electrochemical behavior with a good intra- and inter-electrode reproducibility.




Successive cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $H_2SO_4$  at the **same** thick-film carbon electrode (ED-S1PE-C10).  $v = 50$  mV/s,  $n = 10$ , **RSD = 2%**.




Successive cyclic voltammograms for 1 mM ferrocene methanol in 0.1 M  $H_2SO_4$  at the **same** thick-film carbon electrode (ED-S1PE-C10).  $v = 50$  mV/s,  $n = 10$ , **RSD = 2%**.




Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $H_2SO_4$  at **different** thick-film carbon electrode (ED-S1PE-C10).  $v = 50$  mV/s,  $n = 10$ , **RSD = 2%**.



Cyclic voltammograms for 1 mM ferrocene methanol in 0.1 M  $H_2SO_4$  at **different** thick-film carbon electrode (ED-S1PE-C10).  $v = 50$  mV/s,  $n = 10$ , **RSD = 2%**.



Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $H_2SO_4$  using **different scan rates** at a thick-film carbon electrode (ED-S1PE-C10).




Cyclic voltammograms for 1 mM ferrocene methanol in 0.1 M  $H_2SO_4$  using **different scan rates** at a thick-film carbon electrode (ED-S1PE-C10).


## » Thick-film graphene single-electrodes

**Graphene** (Ref. ED-S1PE-CG) thick-film electrochemical sensors are based on a classical three-electrodes (working – WE, reference – RE and auxiliary – AE) approach.


### » Electrochemical S1PE sensor design




### » Electrochemical cell



**Thick-film graphene-based electrodes** have a very low electrical resistance with a good scratch resistance for using in a wide variety of applications, including the development of low-cost *chemical-sensors* and *bio-sensors* for field analysis.



*Cyclic voltammograms for 1 mM ferrocene methanol in 0.1 M H<sub>2</sub>SO<sub>4</sub> at the **same** thick-film graphene electrode.  
v = 50 mV/s.*




*Cyclic voltammograms for 1 mM hydroquinone in 0.1M H<sub>2</sub>SO<sub>4</sub> at different thick-film **carbon** (ED-S1PE-C10 / ED-S1PE-C20) and activated **graphene**-based electrodes (ED-S1PE-CG20). v = 50 mV/s.*


## » Thick-film gold single-electrodes

**Gold** (Ref. ED-S1PE-Au) thick-film electrochemical sensors are based on a classical three-electrodes (working – WE, reference – RE and auxiliary – AE) approach.


### » Electrochemical S1PE gold sensor design




### » Electrochemical cell



**Thick-film gold-based electrodes** show an excellent electrochemical behavior with a good intra- and inter-electrode reproducibility. **Gold-based electrodes** are very useful for building *self-assembled monolayers* (SAM) and the development of *chemical sensors* and *biosensors*.



Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $H_2SO_4$  at **different** thick-film gold electrodes.  
 $v = 50$  mV/s,  $n = 5$ , **RSD = 2%**.




Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $H_2SO_4$  using **different scan rates** at a thick-film carbon electrode.


## » Thick-film platinum single-electrodes

Platinum (Ref. ED-S1PE-Pt) thick-film electrochemical sensors are based on a classical three-electrodes (working – WE, reference – RE and auxiliary – AE) approach.


### » Electrochemical S1PE platinum sensor design



### » Electrochemical cell




Thick-film platinum-based electrodes show an excellent electrochemical behavior with a good intra- and inter-electrode reproducibility. Platinum-based electrodes exhibit excellent chemical and environmental resistance and are suitable for the development of *chemical sensors* and *biosensors*.



Successive cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M KCl at the **same** thick-film platinum electrode.

$v = 50 \text{ mV/s}$ ,  $n = 10$ , **RSD = 1%**.




Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M KCl at **different** thick-film platinum electrodes.  $v = 50 \text{ mV/s}$ ,  $n = 10$ , **RSD = 3%**.

## » Thick-film single-electrodes selection

Screen-printed single electrodes (S1PE) are available in different electrode materials and substrates.

SKU	Substrate	WE	RE	AE
» ED-51PE-C10	PET	Carbon	Silver	Carbon
» ED-51PE-C10C	Ceramic	Carbon	Silver	Carbon
» ED-51PE-C20	PET	Carbon	Silver	Carbon
» ED-51PE-C20C	Ceramic	Carbon	Silver	Carbon
» ED-51PE-C21	PET	Carbon	Silver/Silver Chloride	Carbon
» ED-51PE-C21C	Ceramic	Carbon	Silver/Silver Chloride	Carbon
» ED-51PE-CG20	PET	Graphene	Silver	Graphene
» ED-51PE-CG20C	Ceramic	Graphene	Silver	Graphene
» ED-51PE-CG21	PET	Graphene	Silver/Silver Chloride	Graphene
» ED-51PE-CG21C	Ceramic	Graphene	Silver/Silver Chloride	Graphene
» ED-51PE-Au10	PET	Gold	Silver	Gold
» ED-51PE-Au10C	Ceramic	Gold	Silver	Gold
» ED-51PE-Pt20	PET	Platinum	Silver	Platinum
» ED-51PE-Pt20C	Ceramic	Platinum	Silver	Platinum



Screen-printed electrodes can be easily **customized** with specific designs and requirements. MicruX has wide experience in the design and development of different thick-film based electrodes. Thus, the electrodes are adapted to fulfill the requirements of customers.


*Note: All combinations are NOT available. Please always check the availability for your specific needs.*

## 1.1.2. Thick-film mediated single-electrodes (S1PE)


### » Thick-film carbon-mediated electrodes

**Mediated** (Ref. ED-S1PE-C/MED) thick-film electrochemical sensors are based on a classical three-electrodes (working – WE, reference – RE and auxiliary – AE) approach.

#### » Electrochemical S1PE mediated-sensor design




#### » Electrochemical cell




#### » MEDIATORS


##### Potassium Ferrocyanide




##### Prussian Blue



##### Cobalt(II) Phthalocyanine




##### Meldola Blue




Carbon-mediated electrodes have been optimized to provide superior electrochemical performance, enabling the detection of many analytes when used in conjunction with specific enzymes (*oxidases* or *dehydrogenases*). Mediated-electrodes are suitable for improving the detection of *hydrogen peroxide* (S1PE-C20/MED) or *NADH* (S1PE-C30/MED) and the development of *enzyme-based biosensors*.

SKU	Substrate	WE	RE	AE
» ED-S1PE-C20/FeCN	PET	Carbon/K <sub>4</sub> Fe(CN) <sub>6</sub>	Silver	Carbon
» ED-S1PE-C20/PB	PET	Carbon/Prussian Blue	Silver	Carbon
» ED-S1PE-C20/CoPc	PET	Carbon/Cobalt Phthalocyanine	Silver	Carbon
» ED-S1PE-C30/MB	PET	Carbon/Meldola Blue	Silver	Carbon


## » Thick-film carbon-mediated electrodes performance




Amperometric response for 10  $\mu\text{M}$  to 5 mM  $\text{H}_2\text{O}_2$  using different thick-film Carbon/Prussian Blue electrodes (ED-S1PE-C20/PB).  $E_d = -0.1$  V, BGE: PBS pH = 7.4.




Amperometric response for 1  $\mu\text{M}$  to 5 mM  $\text{H}_2\text{O}_2$  using different thick-film Carbon/Cobalt Phthalocyanine electrodes (ED-S1PE-C20/CoPc).  $E_d = +0.4$  V, BGE: PBS pH = 7.4.




Successive injections of 100  $\mu\text{M}$   $\text{H}_2\text{O}_2$  in a FIA system using a thick-film Carbon/Prussian Blue electrode (ED-S1PE-C20/PB).  $E_d = -0.1$  V, flow rate: 2 mL/min, carrier: PBS pH = 7.4. RSD = 3.0% (n = 10).



Successive injections of 100  $\mu\text{M}$   $\text{H}_2\text{O}_2$  in a FIA system using a thick-film Carbon/Cobalt Phthalocyanine electrode (ED-S1PE-C20/CoPc).  $E_d = +0.4$  V, flow rate: 2 mL/min, carrier: PBS pH = 7.4. RSD = 2.5% (n = 10).



Successive injections of 100  $\mu\text{M}$   $\text{H}_2\text{O}_2$  in a FIA system using a thick-film Carbon/Potassium Ferrocyanide electrode (ED-S1PE-C20/FeCN).  $E_d = -0.1$  V, flow rate: 1 mL/min, carrier: PBS pH = 7.4. RSD = 4.5% (n = 12).




Successive injections of 100  $\mu\text{M}$  NADH in a FIA system using a thick-film Carbon/Meldola Blue electrode (ED-S1PE-C30/MB).  $E_d = +0.1$  V, flow rate: 2 mL/min, carrier: PBS pH = 7.4. RSD = 2.0% (n = 10).

### 1.1.3. Thick-film dual-electrodes (D2PE)


#### » Thick-film carbon dual-electrodes

**Carbon** (Ref. ED-D2PE-C10) thick-film electrochemical *dual*-sensors are based on a four-electrodes approach with two working electrodes (WE1 / WE2), sharing a reference (RE) and an auxiliary (AE) electrode.


#### » Electrochemical D2PE sensor design




#### » Dual electrochemical cell



Thick-film carbon dual-electrodes show an excellent electrochemical behavior with a good intra- and inter-electrode reproducibility. Ideal for **multiplexing** analysis.



Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $H_2SO_4$  at thick-film **carbon** dual-electrode.  
 $v = 50$  mV/s,  $n = 20$  (10 + 10), **RSD = 2%**.




Cyclic voltammograms for 1 mM ferrocene methanol in 0.1 M  $H_2SO_4$  at thick-film **carbon** dual-electrode.  
 $v = 50$  mV/s,  $n = 20$  (10 + 10), **RSD = 2%**.


## » Thick-film gold dual-electrodes

**Gold** (Ref. ED-D2PE-Au10) thick-film electrochemical *dual*-sensors are based on a four-electrodes approach with two working electrodes (WE1 / WE2), sharing a reference (RE) and an auxiliary (AE) electrode.


### » Electrochemical D2PE sensor design




### » Dual electrochemical cell



Thick-film gold dual-electrodes show an excellent electrochemical behavior with a good intra- and inter-electrode reproducibility. Ideal for **multiplexing** analysis.



Cyclic voltammograms for 1 mM ferrocene methanol in 0.1 M  $H_2SO_4$  at the **same** thick-film gold dual-electrode.  
 $v = 50\text{ mV/s}$ ,  $n = 20$  (10 + 10), **RSD = 2%**.



Cyclic voltammograms for 1 mM ferrocene methanol in 0.1 M  $H_2SO_4$  at **different** thick-film gold dual-electrodes.  $v = 50\text{ mV/s}$ ,  $n = 20$  (10 + 10), **RSD = 2%**.

## 1.2. THIN-FILM ELECTRODES

MicruX develops **metal-based (micro)electrodes** fabricated by thin-film technologies on a Glass substrate. A resin-based protective layer is used to delimit the electrochemical cell enabling the use of very small sample volume.

### » Thin-film electrodes main features



» <b>Standard dimensions:</b>	10 x 6 x 0.7 mm
» <b>Substrate:</b>	Glass
» <b>Protective layer:</b>	SU8/PI resin
» <b>Electrochemical cell:</b>	2 or 3.5 mm Ø
» <b>Sample volume:</b>	1 – 10 µL
» <b>Electrode material:</b>	Platinum or Gold

The inherent properties of the **thin-film (micro)electrodes** such as low cost & disposables, reusable, high fabrication resolution, high sensitivity, low reagent consumption as well as non-tedious pre-cleaning procedures provide a suitable tool for **multiple applications**.

Electroanalysis	Flow Systems & Microfluidics	Nanotechnology	Biosensors
✓ Study EC reactions	✓ FIA Systems	✓ Modified electrodes	✓ EC transducers
✓ Trace EC Analysis	✓ Microchips Electrophoresis	✓ New nanostructures	✓ New recognition elements
✓ In-vivo measurements	✓ Capillary Electrophoresis	✓ New nanomaterials	✓ POC systems
✓ Redox cycling	✓ HPLC		

Electrochemical sensors are available in different standard designs and materials.


*Thin-film technologies can be also used for the manufacture of **customized electrochemical sensors**. MicruX has wide experience in the design and development of different thin-film based electrodes. Thus, the (micro)electrodes are adapted to fulfill the requirements of customers.*

## 1.2.1. Thin-film single-electrodes (SE)


### » Thin-film platinum & gold single-electrodes

Electrochemical sensors SE are based on a three-electrode (working - WE, reference - RE and auxiliary - AE) approach. The three electrodes are fabricated in the same material (*platinum* or *gold*) with high precision and resolution.

#### » Electrochemical SE sensor design




#### » Electrochemical cell (2 mm Ø)




Reference	Electrodes Material	WE size	Electrodes thickness
» ED-SE1-Pt	Titanium / Platinum	1mm diameter	50/150 nm
» ED-SE1-Au	Titanium / Gold	1mm diameter	50/150 nm

Thin-film metal-based electrodes show an excellent electrochemical behavior with a good intra- and inter-electrode reproducibility.



Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $KCl$  at different thin-film Pt electrodes (ED-SE1-Pt).

$v = 50$  mV/s,  $n = 5$ , **RSD = 4%**.




Cyclic voltammograms for 1 mM ferrocenylmethyl alcohol in 0.1 M  $H_2SO_4$  at different thin-film Au electrodes (ED-SE1-Au).  $v = 50$  mV/s,  $n = 4$ , **RSD = 6%**.


## » Thin-film double-metal single-electrodes

Double-metal thin-film electrochemical sensors are based on a three-electrodes approach with a *gold* working electrode (WE) and *platinum* reference (RE) and auxiliary (AE) electrodes. The combination of **two different metal electrodes** in the same EC cell enables the *modification* of the working electrode surface selectively without affecting the surface of the reference and auxiliary electrodes.

### » Electrochemical double-metal SE sensor design




### » Electrochemical cell (2 mm Ø)




Reference	WE	Electrodes Material RE	AE	WE size	Electrodes thickness
» ED-SE1-AuPt	Ti / Au	Ti / Pt	Ti / Pt	1mm diameter	50/150 nm

Thin-film double-metal electrodes show an excellent electrochemical behavior with a good reproducibility.




Successive cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $KCl$  at the **same** thin-film Au electrode (ED-SE1-AuPt).  $v = 50$  mV/s,  $n = 10$ , **RSD = 3%**.



Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $KCl$  using different **scan rates** at a thin-film Au electrode (ED-SE1-AuPt).

## 1.2.2. Thin-film microelectrode arrays (MEA)


Thin-film technologies enable the development of small microstructures ( $<25 \mu\text{m}$ ) with high resolution and precision. Thus, a **microelectrode array** (MEA) based on **pinholes** with a honeycomb microstructure can be manufactured on a working single-electrode.



The working electrode ( $1 \text{ mm diameter}$ ) is based on a metal surface coated with SU-8 resin in which is defined a **microholes array** with **honeycomb structure**.

Reference	Electrodes Material	Working Electrode Microstructure μHoles diameter	μHoles pitch	μHoles number	Electrodes thickness
» ED-mSE-5-Pt	Ti / Pt	5 $\mu\text{m}$	50 $\mu\text{m}$	500	50/150 nm
» ED-mSE-10-Pt	Ti / Pt	10 $\mu\text{m}$	100 $\mu\text{m}$	90	50/150 nm
» ED-mSE-5-Au	Ti / Au	5 $\mu\text{m}$	50 $\mu\text{m}$	500	50/150 nm
» ED-mSE-10-Au	Ti / Au	10 $\mu\text{m}$	100 $\mu\text{m}$	90	50/150 nm

Thin-film **MEA** electrodes show the typical **microelectrode behavior** to enhance the analytical signals by reaching the **steady-state** in a short time.




Cyclic voltammogram for 1 mM ferrocenylmethyl alcohol in 0.1 M  $\text{H}_2\text{SO}_4$  at a thin-film **gold** microelectrode array (ED-mSE-10-Au).  $v = 10 \text{ mV/s}$ .

Electrode pre-cleaning by cyclic voltammetry between -1.5V and +1.5 V ( $n = 10$ ,  $v = 100 \text{ mV/s}$ ) – BGE: 0.1 M  $\text{H}_2\text{SO}_4$ .


### 1.2.3. Thin-film interdigitated electrodes (IDE)

Thin-film technologies enable the fabrication of microelectrodes ( $<25\ \mu\text{m}$ ) with high resolution and precision. The most basic **interdigitated electrodes (IDE)** consist of **two individually addressable microelectrode array strips with an interdigitated approach**. Non-additional reference and auxiliary electrodes are included on the device.

» Electrochemical IDE sensor design



» Electrochemical cell (3.5 mm Ø)



Different interdigitated electrode (IDE) designs are available in platinum or gold.

Reference	Material	µElectrode width	µElectrode gap	Number of feet	Thickness
» ED-IDE1-Pt	Ti/Pt	10 µm	10 µm	90 pairs	50/150 nm
» ED-IDE2-Pt	Ti/Pt	10 µm	5 µm	120 pairs	50/150 nm
» ED-IDE3-Pt	Ti/Pt	5 µm	5 µm	180 pairs	50/150 nm
» ED-IDE1-Au	Ti/Au	10 µm	10 µm	90 pairs	50/150 nm
» ED-IDE2-Au	Ti/Au	10 µm	5 µm	120 pairs	50/150 nm
» ED-IDE3-Au	Ti/Au	5 µm	5 µm	180 pairs	50/150 nm

These lineal-band electrodes have been specially designed in a circular cell to work with very small sample drops ( $< 10\ \mu\text{L}$ ). The sample drop shape is well-adapted to the electrode cell in order to get the maximum performance and precision.



The interdigitated electrodes (IDE) provide a suitable tool especially useful for **impedance**, **capacitance** and **conductivity** measurements as well as **fuel cells**.

Electrochemical Impedance Spectroscopy (EIS) is a powerful, fast and accurate non-destructive method that can be used with the interdigitated electrodes (IDE) in **multiple** analytical **applications**.

» Gold thin-film interdigitated electrodes



» Platinum thin-film interdigitated electrodes

### Nyquist Plots



Nyquist plots using **different** gold and platinum thin-film **interdigitated electrodes** in a low conductivity NaCl solution (6.0 mS/cm). Frequencies range: 500 kHz – 100 Hz,  $V_{p-p} = 25$  mV. **Inset:** equivalent electric circuit.

### Bode Plots




Bode plots using **different** gold and platinum thin-film **interdigitated electrodes** in a low conductivity NaCl solution (6.0 mS/cm). Frequencies range: 500 kHz – 100 Hz,  $V_{p-p} = 25$  mV.

\*Impedance spectra data were provided by Nanobiotechnology for Diagnostics (Nb4D) Group from Advanced Chemical Research Institute of Catalonia (IQAC-CSIC), Biomedical Research Networking Center in Bioengineering, Biomaterials and Nanomedicine (CIBER-BBN), Barcelona, SPAIN.


## 1.2.4. Thin-film interdigitated microelectrode array (IDA)

Thin-film technologies enable the integration of the *reference* (RE) and *auxiliary* (AE) electrodes with the interdigitated microelectrodes. **Interdigitated array** (IDA) electrodes take also advantages of the microelectrode features enhancing the *sensitivity* and *detection limits*. In this case, the working electrode (WE) consists of **two individually addressable arrays** of microelectrodes with an interdigitated approach.

» Electrochemical IDA sensor design



» Electrochemical cell (2 mm Ø)




### » IDA working electrode


Different IDA microelectrode (WE1/WE2) designs are available in platinum or gold.

Reference	Material	µElectrode width	µElectrode gap	Number of feet	Thickness
» ED-IDA1-Pt	Ti/Pt	10 µm	10 µm	15 pairs	50/150 nm
» ED-IDA5-Pt	Ti/Pt	10 µm	5 µm	20 pairs	50/150 nm
» ED-IDA6-Pt	Ti/Pt	5 µm	5 µm	30 pairs	50/150 nm
» ED-IDA1-Au	Ti/Au	10 µm	10 µm	15 pairs	50/150 nm
» ED-IDA5-Au	Ti/Au	10 µm	5 µm	20 pairs	50/150 nm
» ED-IDA6-Au	Ti/Au	5 µm	5 µm	30 pairs	50/150 nm


Thin-film IDA electrodes could be used in **single-** (only one WE, *generator*, is connected) or **dual-mode** (both WEs, *generator* and *collector*, are connected). **Dual-mode** enables the **microelectrode behavior**, reaching the **steady-state** in a short time and **enhancing** the analytical signals.



IDA microelectrode designs (*width and gap*) are going to affect the number of *redox cycling* as well as the *collection efficiency*.



Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $KCl$  using **single-** and **dual-mode** at different **Platinum** IDA electrodes.




Cyclic voltammograms for 1 mM ferrocene methylalcohol in 0.1 M  $H_2SO_4$  using **single-** and **dual-mode** at different **Gold** IDA electrodes.

**Generator (WE1)** potential cycled from -0.3 to 0.5 V at 50 mV/s. **Collector (WE2)** potential held constant at -0.3 V (dual-mode).


### 1.2.5. Thin-film interdigitated ring array (IDRA)

Thin-film technologies open the gate to develop special microelectrodes designs. **Interdigitated ring array (IDRA)** electrodes bring a radial design specially focused on flow systems. The working electrode consists of **two radial arrays of microelectrodes** with an interdigitated approach.

» Electrochemical IDRA sensor design




» Electrochemical cell (2 mm Ø)




» IDRA working electrode

Reference	Material	µElectrode width	µElectrode gap	Number of feet	Thickness
» ED-IDRA1-Pt	Ti/Pt	10 µm	10 µm	12 pairs	50/150 nm
» ED-IDRA1-Au	Ti/Au	10 µm	10 µm	12 pairs	50/150 nm

Dual-mode enables the **microelectrode behavior**, reaching the **steady-state** in a short time and **enhancing** the analytical signals



Cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M  $KCl$  using **single-** and **dual-mode** at a **Platinum IDRA** electrode.



Cyclic voltammograms for 1 mM ferrocene methylalcohol in 0.1 M  $H_2SO_4$  using **single-** and **dual-mode** at a **Gold IDRA** electrode.


## 1.2.6. On-demand thin-film electrochemical sensors

MicruX is able to manufacture *off-the-shelf* metal-based thin-film (micro)electrodes as well as other *pre-designed sensors on-demand*. Different *on-demand sensors* are currently available to be manufactured. Metal-based (micro)electrodes are manufactured on a glass substrate with a resin (SU8/PI) as insulating layer, delimiting the electrochemical cell.


### » Basic Single- & Multi-Electrode Systems

Different single- and multi-electrode chips, integrating one or more working electrodes (WE) as well as reference (RE) and auxiliary (AE) electrodes, are easily manufactured by using thin-film technologies. Electrodes are available in gold and platinum.


#### » Single-Sensor



#### » Dual-Sensor




#### » Tri-Sensor




## » Basic Interdigitated Lineal & Ring Electrodes

Different lineal (IDE) and ring (IDRE) approaches are available for the basic interdigitated electrodes. Interdigitated electrodes consist of two individually addressable microelectrode array strips.

### » IDE sensors




### » IDRE sensors




## » Dual Interdigitated Lineal & Ring Electrodes

Dual interdigitated electrodes (lineal or ring) can be integrated in a single chip with different configurations.

### » Dual-IDE sensors



### » Dual-IDRE sensors




 [more info](#)

## » Individually Addressable MicroElectrode Arrays


Thin-film technologies enable the manufacture of different individually addressable multi-electrode array (iMEA) systems.

### » iMEA chip



**iMEA chip** consists of four sets of seven 10- $\mu\text{m}$  microelectrodes (28 individually addressable microelectrodes) with integrated reference and auxiliary electrodes in the center of the chip.

### » multi-iMEA chip




**Multi-iMEA chip** consists of four areas with seven sets of seven 10- $\mu\text{m}$  microhole arrays (28 individually addressable microelectrode arrays) with integrated reference and auxiliary electrodes in the center of the chip.


## » Multi-Electrodes Chips

Thin-film technologies enable the integration of multiple electrochemical cells in a single chip for multiplexing detection.

### » 8x single-electrode chip




### » 16x single-electrode chip



## » Multi Interdigitated Electrodes Chips

Thin-film technologies also enable the integration of multiple cells with interdigitated electrodes in a single chip for multiplexing detection.

### » Multi-IDE chip




more info

## 1.3. MANUFACTURING SERVICES

MicruX is a leading developer in innovative electrochemical and microfluidic solutions. We offer a wide range of custom solutions to meet your specific needs. Our experienced team of engineers can work with you to design and **manufacture** devices that are **tailored** to your application.

As a trusted partner, we support you from the very early stages through to final device serial production, offering complete services or handling specific phases as needed.



### » Our Expertise

At MicruX, we leverage advanced technologies and years of expertise to deliver high-quality custom solutions. Our team is dedicated to meeting your specific needs with precision and efficiency.

### » Why Choose Us

- ✓ Cutting-edge technology
- ✓ Personalized service
- ✓ High-quality standards
- ✓ Fast turnaround times

At MicruX, we are committed to providing top-notch services throughout the entire journey of your microfluidic and electrochemical sensor project. Let us help you bring your vision to life!

### 1.3.1. Thin-film electrodes manufacturing services

MicruX excels in the design and manufacturing of **thin-film electrodes** tailored to your specific needs. Our state-of-the-art thin-film technology ensures precision, reliability, and high performance for a wide range of applications.

#### » Advanced Thin-film Technology

Utilizing the latest advancements in thin-film deposition techniques, we create electrodes that meet the highest industry standards.

#### » Quality Assurance

Every electrode undergoes rigorous testing to ensure it meets your specifications and performs reliably in real-world conditions.

#### » Technical Specifications / Customization Options



» <b>Substrate:</b>	Glass Wafers
» <b>Electrode materials:</b>	Platinum or Gold thin-films
» <b>Minimal electrode features:</b>	up to 5 µm
» <b>Typical electrode thickness:</b>	150 ± 15 nm
» <b>Protective layer:</b>	SU8/PI resin

#### » Applications

Thin-film electrodes are a very useful analytical tool for **multiple applications**, taking advantages of their inherent properties such as low cost & disposables, reusable, high fabrication resolution, high sensitivity, low reagent consumption as well as non-tedious pre-cleaning procedures.



Biosensing



Environmental Monitoring



Industrial Process Control



Point-of-Care Diagnostic

### 1.3.2. Printed electrodes manufacturing services

MicruX is specialized in the fabrication of high-quality **printed electrodes** using advanced screen-printing techniques. Our printed electrodes offer cost-effective solutions with excellent performance and flexibility for various applications.

#### » Screen-Printing Technology

We employ cutting-edge screen-printing technology to produce electrodes with high precision and consistency.

#### » Quality Control

Our printed electrodes undergo strict quality control measures to ensure they meet the highest standards of performance and durability.

#### » Technical Specifications / Customization Options



» <b>Substrate:</b>	Flexible Polyester (white or clear) Rigid Alumina ( $\text{Al}_2\text{O}_3$ )
» <b>Substrate thickness:</b>	PET (white): 125 / 250 / 350 $\mu\text{m}$ PET (clear): 125 / 175 $\mu\text{m}$ Alumina: 380 $\mu\text{m}$
» <b>Electrode materials:</b>	Carbon / Graphene / Silver / Silver-Silver Chloride / Gold / Platinum
» <b>Min. electrode features:</b>	500 $\mu\text{m}$

#### » Applications

Printed electrodes are a suitable tool for **multiple applications**, providing many advantages such as low-cost, disposable, low reagent consumption as well as non-tedious pre-cleaning procedures.



Biosensing



Environmental Monitoring



Industrial Process Control



Point-of-Care Diagnostic

### 1.3.3. Microfluidic manufacturing services

MicruX is specialized in fabricating **microfluidic SU-8 master molds** on silicon wafers. Our master mold manufacturing services provide a cost-effective and versatile tool for creating soft casting polymers (like PDMS) and for hot-embossing processes. These master molds ensure high fidelity in replicating intricate designs, making them ideal for diverse microfluidic applications

SU8 microstructures can be manufactured on a 4-inch silicon wafer in order to get master molds with high precision and resolution (up to  $5\text{-}\mu\text{m}$  minimal features). These master molds are created with high precision and resolution, ensuring that every detail of your design is accurately reproduced. This technology is essential for producing reliable and high-performance microfluidic devices.


#### » Multilayer and 3D Microfluidics

Our capabilities extend to the manufacturing of multilayer structures (*up to 2 SU-8 layers*), including **3D microfluidics**. These complex designs enable advanced functionalities and greater flexibility in your microfluidic applications, providing solutions that can meet the most demanding requirements



Silicon wafer could be cut on smaller rectangular pieces in order to get individual masters. Other technical features can be fulfilled under request.

#### » Technical Specifications



» <b>Substrate:</b>	4-inch Silicon wafers
» <b>Structures:</b>	SU-8 resin
» <b>Minimal features:</b>	Height: 5 $\mu\text{m}$ / Width: 5 $\mu\text{m}$
» <b>Max. features:</b>	Up to 300 $\mu\text{m}$ (single-layer)
» <b>Typical aspect ratio:</b>	1:1 (Width:Height)
» <b>Structures layers:</b>	Up to 2-layers

Our microfluidic solutions are perfect for applications in lab-on-a-chip systems, chemical analysis, medical diagnostics, environmental monitoring, and more.

## 1.4. ELECTROCHEMICAL & MICROFLUIDIC PLATFORMS

### 1.4.1. Drop-cell interface

The drop-cell connector (**Ref. ED-DROP-CELL**) provides a true user-friendly interface with the potentiostat, enabling the use of microvolume (1 – 10 µL sample drops) with all standard (10 x 6 mm) thin-film (micro)electrodes.



- » **Dimensions:** 40 x 30 x 25 mm (WxDxH)
- » **Material:** aluminium base + methacrylate cover
- » **User friendly** (tool free assembly).
- » **Easy and fast replacement** of the electrodes.
- » **High quality** robust connector.
- » **Reusable** – long-life.

The drop-cell connector and AIO-cell (**ref. ED-AIO-CELL**) are supplied with a universal cable compatible with any commercial potentiostat.

#### » Cable Terminals



miniUSB to Drop-cell / AIO-cell

#### 2-mm Male or Female banana plug to potentiostat



*Plug to potentiostat may be available in another format under previous request.*

### 1.4.2. All-in-One Platform for thin-film electrodes


The innovative All-in-One cell (**ref. ED-AIO-CELL**) provides a unique multipurpose interface with movable add-ons that can be easily interchanged for using the standard (10 x 6 mm) thin-film (micro)electrodes.



- » **Dimensions:** 60 x 40 x 30 mm (WxDxH)
- » **Material:** aluminium base + methacrylate cover/add-ons
- » **Easy and fast electrode replacement.**
- » Different **movable** Add-Ons.
- » **Easy Add-Ons assembly** (tool free).
- » **Reusable** – long life.

The AIO-cell enables the use of the thin-film (micro)electrodes in **static (Drop / Batch-cell)** or **dynamic (Flow-cell)** conditions, fulfilling the requirements of **multiple** analytical **applications**.

#### Movable Add-Ons



The AIO-cell is currently provided in two versions, the base cell + one add-on (**ref. ED-AIO-CELL-1x**) or the base cell + two add-ons (**ref. ED-AIO-CELL-2x**). Additional **add-ons** in **PMMA** (standard) or **PEEK** (on demand) can be provided with the base cell. The add-ons can be also supplied by separated and they can be customized (*materials / designs*) considering the specific requirements of the customers.



 [more info](#)

Different **Flow-cell** and **Batch-cell** add-ons in **PMMA** (standard) and **PEEK** (on demand) are currently available for using in combination with the AIO platform and all standard (10 x 6 mm) thin-film (micro)electrodes.

## » AIO add-ons



### » Batch-cell Add-ons

- ❖ **BC-PMMA-5,0 / BC-PEEK-5,0.** Compatible with all thin-film (micro)electrodes and IDμElectrodes with 2- or 3,5-mm diameter electrochemical cell.


The cell is sealed with a 5 mm I.D. O-ring.



### » Flow-cell Add-ons

- ❖ **FC-PMMA-2,0 / FC-PEEK-2,0.** Compatible with thin-film (micro)electrodes with 2 mm diameter electrochemical cell. The cell is sealed with a 2 mm I.D. O-ring.
- ❖ **FC-PMMA-3,5 / FC-PEEK-3,5.** Compatible with thin-film IDμElectrodes with 3,5 mm diameter electrochemical cell. The cell is sealed with a 3,5 mm I.D. O-ring

Amperometric measurements in a **Flow Injection Analysis** (FIA) system using the **AIO cell** with **add-on FC-PMMA-2,0** and MicruX **ECStat** instrument (*ref. ECSTAT2020*).



Successive injections of  $1 \cdot 10^{-5}$  M pAP in the FIA system using a **thin-film Pt single-electrode** (ED-SE1-Pt). Carrier: 0.1 M PBS, pH = 7.4, flow rate = 1 mL/min,  $E_d$  = +0.4 V. **RSD** = 4%,  $n$  = 10.

### 1.4.3. All-in-One SPE Platform for thick-film electrodes


A multipurpose All-in-One platform ([ref. ED-AIO-SPE-CELL](#)) with movable add-ons is also available for using the standard (27.5 x 10.1 mm) thick-film electrodes.




- » **Dimensions:** 60 x 40 x 30 mm (WxDxH)
- » **Material:** aluminium base + methacrylate add-ons
- » **Easy and fast electrode replacement.**
- » **Different movable Add-Ons.**
- » **Easy Add-Ons assembly (tool free).**
- » **Reusable** – long life.

The **AIO-SPE-cell** enables the use of the thick-film electrodes in **static** (*Batch-cell*) or **dynamic** (*Flow-cell*) conditions, fulfilling the requirements of **multiple** electroanalytical **applications**.

#### Movable Add-Ons



**Flow-cell Add-on**



**Batch-cell Add-on**

The **AIO-SPE-cell** is currently provided in two versions, the base cell + one add-on ([ref. ED-AIO-SPE-CELL-1x](#)) or the base cell + two add-ons ([ref. ED-AIO-SPE-CELL-2x](#)).

The **AIO-SPE-cell** is compatible with the **SPE-CABLE connector** ([ref. ED-SPE-CABLE](#)) for interfacing the electrodes with the potentiostat. This cable is supplied with the platform.



 [more info](#)

#### 1.4.4. Multi8x All-in-One Platform

The Multi8x All-in-One cell ([ref. ED-MULTI8x-AIO-CELL](#)) provides a **multiplexing** interface with movable add-ons that can be easily interchanged for using up to **eight** thin-film (micro)electrodes.



- » **Dimensions:** 120 x 40 x 30 mm (WxDxH)
- » **Material:** aluminium base + methacrylate cover/add-ons
- » **Easy and fast electrode replacement.**
- » Different **movable** Add-Ons.
- » Add-Ons **assembly** by screws.
- » **Reusable** – long shelf-life.

The multi8x AIO-cell enables the use of up to **eight** thin-film (micro)electrodes in **static** (*Drop / Batch-cell*) or **dynamic** (*Flow-cell*) conditions, providing a **multiplexed detection** system in several applications.

##### Movable Add-Ons



**Multi-Flow-cell Add-ons**



**Multi- Batch-cell Add-ons**

The Multi8x AIO-cell is currently provided in two versions, the base cell + one add-on ([ref. ED-MULTI8x-AIO-CELL-1x](#)) or the base cell + two add-ons ([ref. ED-MULTI8x-AIO-CELL-2x](#)). Additional add-ons in **PMMA (standard)** or **PEEK (on demand)** can be provided with the base cell. The add-ons can be also supplied by separated and they can be customized (*materials / designs*) considering the specific requirements of the customers.

Different **Multi-flow-cell** and **Multi-batch-cell** add-ons in **PMMA** (*standard*) and **PEEK** (*on demand*) are currently available for using in combination with the multi8x AIO platform and all standard (10 x 6 mm) thin-film (micro)electrodes.

## » Multi8x AIO add-ons



### » Multi-batch-cell Add-ons


- ❖ **Multi8x-BC-PMMA-5,0 / Multi8x-BC-PEEK-5,0.** Compatible with thin-film (micro)electrodes with 2 mm or 3,5 mm diameter electrochemical cell. The cell is sealed with a 5 mm I.D. O-ring.  
*The batch cell add-on features correspond to a column (A → H) of a 96-well microplate with up to 400 µL per well.*



### » Multi-Flow-cell Add-ons

- ❖ **Multi8x-FC-PMMA-2,0 / Multi8x-FC-PEEK-2,0.** Compatible with thin-film (micro)electrodes with 2 mm diameter electrochemical cell. The cell is sealed with a 2 mm I.D. O-ring.
- ❖ **Multi8x-FC-PMMA-3,5 / Multi8x-FC-PEEK-3,5.** Compatible with thin-film IDµElectrodes with 3,5 mm diameter electrochemical cell. The cell is sealed with a 3,5 mm I.D. O-ring

Multi8x AIO platform enable the simultaneous or sequential employment of up to **eight electrode chips** in static (*see Figure*) or dynamic (flow-system) conditions by using a multi-potentiostatic station.



*Simultaneous* cyclic voltammograms for 1 mM  $K_4Fe(CN)_6$  in 0.1 M KCl using **eight (from A to H)** different **thin-film Pt electrodes** (ED-SE1-Pt) with the **Multi8x AIO-cell**.  $v = 50$  mV/s,  $RSD < 5\%$ .

### 1.4.5. Multi-electrode Chip Platform

The multi-electrode chip platform ([Ref. ED-ME-CELL](#)) provides a simple and robust interface with a multi-potentiostat for using the thin-film multi-electrode chips developed by MicruX.

- *Multi-electrode platform (main unit)*




- » **Dimensions:** 70 x 95 x 25 mm (WxDxH)
- » **Material:** aluminium base + methacrylate covers
- » **User friendly** (tool free assembly).
- » **Easy and fast replacement** of the electrodes.
- » **Reusable** – long -life.
- » **Compatible** with up to 37x15 mm chips.

The multi-electrode platform consists of a main unit with chip accommodation and electronics, two interconnection boxes and universal cables for interfacing with any commercial multi-potentiostat. The platform enables up to *48 individual connections*. This cable interfacing is also provided with Multi8x AIO platform ([ref. ED-MULTI8x-AIO-CELL](#)).

- *Interconnection box*



- *Cables*




The platform enables the use of **on-demand sensors**, up to two **18.5x15 mm chips** or one **37x15 mm chip**. **Tailored multi-electrode chips** adapted to this platform can be manufactured with the specific requirements of the customers. The **interface** (connector box, cables...) for a specific **multi-potentiostat** can be also **customized**.

### 1.4.6. Other interfaces

**MicruX** provides additional connectors for easy interfacing the thick- and thin-film electrodes with the analytical instrumentation.

#### » CABLE connector for thick-film electrodes (ED-SPE-CABLE)



The **SPE-CABLE** connector (**Ref. ED-SPE-CABLE**) provides an interface between the **thick-film electrodes** (up to four contact pads) with the potentiostat, enabling the use of microvolume (20 – 50  $\mu$ L sample drops) or dipping into a solution. The cable ends are available with 2-mm female or male bananas.

*Dimensions: 50 cm long*

#### » BOX connector for thick-film electrodes (ED-SPE-BOX)



The small **BOX connector** (**Ref. ED-SPE-BOX**) provides an interface between the **thick-film electrodes** (up to four contact pads) with any kind of potentiostat, enabling the use of microvolume (20 – 50  $\mu$ L sample drops). The interface ends are available with 2-mm female bananas.

*Dimensions: L58 x W40 x H15 mm*

#### » SPE adaptor for thick-film electrodes (ED-SPE-ADAPTOR)



**Adaptor** (**Ref. ED-SPE-ADAPTOR**) for 3-pins SPE connectors (from other brands) to interface **MicruX® thick-film electrodes**, which have four contact pads.

This versatile and cost-effective solution allows for the use of our SPEs with various connectors.

## » CABLE connector for thin-film electrodes (ED-TF-CABLE)



The **TF-CABLE connector** (*Ref. ED-TF-CABLE*) provides an interface between the **thin-film electrodes** (up to four contact pads) and the potentiostat, enabling the use of microvolume (2 – 10  $\mu\text{L}$  sample drops) or dipping into a solution. The cable ends are available with 2-mm female or male bananas.

*Dimensions: 50 cm long*

## » CABLE connector for thin-film IDE electrodes (ED-IDE-CABLE)




The **IDE-CABLE connector** (*Ref. ED-IDE-CABLE*) provides an interface between the **thin-film IDE $\mu$ Electrodes** (IDE - two contact pads) with the potentiostat, enabling the use of microvolume (2 – 10  $\mu\text{L}$  sample drops) or dipping into a solution. The cable ends are available with 2-mm female or male bananas.

*Dimensions: 50 cm long*

Other interfaces may be requested for adapting the thick- and thin-film electrodes in a specific experimental set-up.

### 1.4.7. External Electrodes Platform


The EEP Platform (**ref. EEP-AIO-CELL**) enables the use of external electrodes in the AIO-cell in static conditions with the batch-cell add-ons. The EEP Platform simplify the placement of the external electrodes in the AIO-cell to be used with the *MicruX' thick- & thin-film electrodes*.



- » **Dimensions:** 75 x 65 x 35 mm (WxDxH)
- » **Material:** PLA
- » **Easy** AIO-cell fitting.
- » **Different Arms** for the placement of external electrodes.
- » **Easy** and **Fast** arm positioning.
- » **External electrodes** are always placed in the same position

The **EEP Platform** can be used to place just the *external reference electrode* or the *reference and auxiliary electrodes* together.

*Platform with external reference electrode*



*Platform with external reference & auxiliary electrodes*




The platform is compatible with the **external miniaturized electrodes** (*reference & auxiliary electrodes*) provided by MicruX.

MicruX provides **miniaturized reference (Ag/AgCl)** and **auxiliary/counter (Pt or SS)** electrodes for using with MicruX' thick- / thin-film (micro)electrodes and EEP-AIO platform. **External electrodes (reference and auxiliary/counter electrodes)** can be a useful solution in several electroanalytical applications.


## » Reference Electrode – Ag/AgCl

Miniaturized reference electrode consists of a **silver/silver chloride (Ag/AgCl)** wire inserted in a **polypropylene (PP)** body with 3M KCl as supporting electrolyte (**Ref. RE-Ag/AgCl**).




## » Auxiliary/Counter Electrode – Pt

Auxiliary/counter electrodes are made of a highly inert material. Thus, MicruX provides **Platinum Auxiliary/Counter electrodes (Ref. CE-Pt)**.



## » Auxiliary/Counter Electrode – SS

Auxiliary/counter electrodes can be made of other inexpensive materials. Thus, MicruX also provides **Stainless Steel (SS) Auxiliary/Counter electrodes (Ref. CE-SS)**.



## 1.5. INSTRUMENTATION

MicruX provides portable analytical instruments that can be used with thick- & thin-film electrodes as well as any classical electrodes.

### 1.5.1. Miniaturized Electrochemical Workstation

#### » MicruX® ECStat

MicruX ECStat ([ref. ECSTAT2020](#)) is a USB-powered *All-in-One Electrochemical Workstation*, including a Bipotentiostat / Galvanostat with built-in Impedance Analyzer, in a very compact and portable equipment.



- » **Dimensions:** 160 x 100 x 45 mm (L x W x H)
- » **USB-powered**
- » Control PC software - **MicruX EC Manager**
- » **Interfacing:** USB-C
- » **LED indicators:** power on, cell on
- » **Built-in FRA/EIS analyzer:** 10 µHz to 1 MHz
- » **Current ranges:** 100 pA to 10 mA (max. current: ± 30 mA)
- » **Operating modes:** bipotentiostat, potentiostat, ZRA, galvanostat, Potentiostatic-EIS analyzer

#### » MicruX® ECStat – Standard Pack

##### Basic content:

- » Bipotentiostat/Galvanostat/Impedance Analyzer
- » Plastic briefcase
- » Sensor cable with 2-mm banana plugs (+ Alligator clips)
- » USB-C cable
- » Y-USB cable (for BIPOT extra power)
- » Dummy cell
- » MicruX® EC Manager software

##### Additional accessories:

- » Sensor cable with miniUSB plug for MicruX platforms
- » Electrode Pack (30 thin-film electrodes + drop-cell interface)



## » MicruX® ECStat features

### General

» DC-potential range	± 10 V
» Compliance voltage	± 10 V
» Maximum current	± 30 mA

### Potentiostat

» Applied DC-potential resolution	75 µV
» Applied potential accuracy	≤ 0.1% ± 1 mV offset
» Current ranges	100 pA to 10 mA (9 ranges)
» Current accuracy	≤ 0.1 % (at Full Scale Range)
» Measured current resolution	0.006 % of current range (5 fA on 100 pA range)

### Galvanostat

» Current ranges	1 nA to 10 mA (8 ranges)
» Applied DC-current range	± 6 times applied current range
» Applied DC-current resolution	0.005 % of applied current range
» Measured DC-potential accuracy	75 µV at ± 10 V 7.5 µV at ± 1 V 0.75 µV at ± 0.1 V

### EIS (impedance measurements)

» Frequency range	10 µHz to 1 MHz
» AC-amplitude range	1 mV to 250 mV rms, or 0.6 V p-p

### Electrometer

» Electrometer amplifier input	> 1 TΩ // 10 pF
» Bandwidth	1 MHz

### Other

» External inputs/outputs (D-Sub 15)	Iout, Eout 1 Analog input (± 10V, 18 bit) 1 Analog output (0-10 V, 12 bit, 1 kΩ output impedance) 4 Digital outputs (5 V) 1 Digital input (5 V)
» Housing	Aluminium case: 160 x 100 x 45 mm <sup>3</sup>
» Weight	0,5 Kg
» Temperature range	0 °C to + 50 °C
» Power supply	USB power supply
» Communication	USB-C

## » MicruX® ECStat – Available Techniques

### Voltammetry

CV	Cyclic Voltammetry
FSCV	Fast-Scan Cyclic Voltammetry
LSV	Linear Sweep Voltammetry
DPV	Differential Pulse Voltammetry
NPV	Normal Pulse Voltammetry
SWV	Square Wave Voltammetry
ACV	Alternating Current Voltammetry

### Amperometry

AD	Single-Potential DC Amperometry
FA	Fast Amperometry
PAD	Pulsed Amperometric Detection
DPA	Differential Pulse Amperometry
MSA	Multi-Step Amperometry

### Potentiometry

ZCP	Zero Current Potentiometry
PD	Potentiometric Detection
MSP	Multi-Step Potentiometry
PSA	Potentiometric Stripping Analysis

### Impedance (Potentiostatic Mode)

PFP	PEIS – Fixed Potential
PSP	PEIS – Scan Potential
PTS	PEIS – Time Scan


### Bipotentiostat

CV-CV* // CV-AD*
LSV-LSV* // LSV-AD*
AD-AD* // MSA-MSA* // MSA-AD*

\*WE2 potential is fixed or offset from WE1 potential

## » MicruX® EC Manager

**MicruX® EC Manager** provides a modern *graphical user interface* for the control of the instrument from a PC, enabling real-time plotting as well as storage and analysis of the results.



- » Multiple curve options: Save, Load, Export to Excel/CSV/Image
- » Peaks search, baseline corrections, curve operations
- » Multiple EIS spectrum plotting
- » Export EIS data for analysis

Fast load of your favorite methods

## 1.5.2. Ultra-compact Electrochemical Sensing Interface

### » MicruX® ECsens BIPOT

**MicruX ECsens BIPOT** (ref. **ECSENS104/BIPOT**) is the most compact and affordable *Electrochemical Sensing Interface*, integrating a **miniature bipotentiostat**, specially designed for using printed electrodes and other sensors.



- » **Dimensions:** 39 x 17 x 9 mm (L x W x H)
- » **USB-powered**
- » **Control PC software - MicruX EC Manager Lite**
- » **Interfacing:** USB-C
- » **LED indicators:** power on / cell on
- » **Potential range:**  $\pm 1.5$  V
- » **Current ranges:** 0.25  $\mu$ A to 12.5 mA (max. current:  $\pm 5$  mA)
- » **Operating modes:** bipotentiostat / potentiostat (multi-channel mode available)

### » MicruX® ECsens – Available Techniques

<b>Voltammetry</b>	
CV	Cyclic Voltammetry
LSV	Linear Sweep Voltammetry
DPV	Differential Pulse Voltammetry
NPV	Normal Pulse Voltammetry
SWV	Square Wave Voltammetry

<b>Amperometry</b>	
AD	Amperometry (Single-potential)
CA	Chronoamperometry (Multi-step)
<b>Potentiometry</b>	
PSA	Potentiometric Stripping Analysis

*Voltammetric and amperometric methods can be used in BIPOT mode*

### » MicruX® ECsens – Standard Pack

#### Basic content:

- » ECsens ultra-compact bipotentiostat
- » Sensor interface for MicruX screen-printed electrodes (S1PE/D2PE)
- » Electrode Pack (50 units ED-S1PE-C)
- » USB adaptor (USB-C Female to USB-A male)
- » USB extension cable
- » Dummy cell
- » MicruX® EC Manager software Lite



## » MicruX® ECsens features

### General

» DC-potential range	± 1.5 V
» Compliance voltage	± 2.65 V
» Maximum current	± 5 mA

### Potentiostat

» Applied DC-potential resolution	250 µV
» Applied potential accuracy	≤ 0.1%
» Current ranges	0.25 µA to 12.5 mA (5 ranges)
» Current accuracy	≤ 0.1 % (at Full Scale Range)
» Measured current resolution	0.002 % of current range (5 pA on 0.25 µA range)

### Multi-channel mode

» Multiplexing	Up to 256 devices (PC software control)
----------------	---

### Other


» Housing	Aluminium case: 39 x 17 x 9 mm <sup>3</sup>
» Weight	< 5 g
» Power supply	USB (5 VDC / 20 mA max.)
» Communication	USB-C

## » MicruX® EC Manager LITE



**MicruX® EC Manager Lite** is the basic graphical user interface for the control of the device from a PC, enabling real-time plotting, storage and analysis of the results.

The software also enables control of **multiple devices** from same screen and at the same time, setting up parallel replicates and spools for **multiplexing analysis**.

**MicruX® ECsens BIPOT** and **EC Manager Lite** provide a first-class **entry-level** ultra-compact potentiostat for electrochemical studies, development of biosensors and many other applications. A powerful interface with many possibilities.



- » Multiple curve options: Load, Overlay, Export to Excel/Image.
- » Experiment spooling: set up sequential multi-experiments.
- » Multi-channel option: **multiplexing** control up to 256 devices.
- » Curves analysis / Peaks search.



# micrux EC Manager LITE

## 2. ACCESSORIES FOR MICROFLUIDICS & ELECTROCHEMISTRY

---



*MicruX provides several additional **accessories** necessities to suitable work with **microfluidic devices**, **electrochemical sensors** and portable analytical **instrumentation**.*

## 2.1. PUMPING SYSTEMS

Different **pumping systems** are available for the use of **microfluidic** and **electrochemical** solutions provided by MicruX or any other supplier.

### 2.1.1. Multi-channel LP Peristaltic Tube Pump

**Peristaltic pumps** offer a *low-cost* solution with an *excellent performance* for most **lab applications**.

References	BT100-3J	BT100-1F	BT100-1L
<b>Peristaltic pump specifications</b>	 CE	 CE	 CE
» <b>Channels (DG Series):</b>	1-2	1-4	4-24
» <b>Flow rate range:</b>	0.000166 to 32 mL/min	0.002 mL/min to 32 mL/min	
» <b>Speed range:</b>	0.1 -100 rpm, CW/CCW		
» <b>Speed resolution:</b>	0.1 rpm		
» <b>Work Mode:</b>	--	Flow rate and dispensing mode	--
» <b>Display:</b>	3-digit LED display for current speed. 3 LED indicators for operating state	LCD for running state	128 × 64 graphic LCD for current running status
» <b>Control mode:</b>	Membrane keypad, external signal and communication control	Control panel, external signal and communication control	
» <b>External control:</b>	Start/stop, direction and speed control (4-20mA, 0-5V, 0-10V, 0-10kHz external control module optional)		
» <b>Comm. Interface:</b>	RS485		
» <b>Power-off memory:</b>	Return to previous state when power on		
» <b>Prime:</b>	Fast filling or emptying at full speed		
» <b>Power supply:</b>	AC 90V-260V	AC 220 V ± 10% 50/60 Hz (standard) or AC 110 V ± 10% 50/60 Hz (optional)	
» <b>Dimensions (L x W x H):</b>	232 x 142 x 149 mm	285 x 207 x 180 mm	202 x 160 x 239 mm
» <b>Weight:</b>	2.3 Kg	3.8 Kg	5.3 Kg
» <b>Power consumption:</b>	30W	40W	50W
» <b>Operating temperature:</b>	0 to 40 °C		
» <b>Relative humidity:</b>	< 80%		
» <b>IP rate:</b>	IP31		

References	L100-1E	L100-1S	L100-1F
<b>Peristaltic pump specifications</b>			
» <b>Channels (DG Series):</b>	1-2	1-4	
» <b>Flow rate range:</b>	0.000166 to 32 mL/min	0.15 µL/min to 32 mL/min	
» <b>Speed range:</b>	0.1 -100 rpm, CW/CCW	0.01 -100 rpm, CW/CCW	0.1 -100 rpm, CW/CCW
» <b>Speed resolution:</b>	0.1 rpm	0.01 rpm	0.1 rpm
» <b>Work Mode:</b>	--	Speed control and flow rate mode	Programming
» <b>Display:</b>	3-digit LED display for current speed. 2 LED indicators for running direction	LCD	7" 1024*600 color LCD
» <b>Control mode:</b>	Membrane keypad control	Membrane keypad, external signal and communication control	Touch screen control, footswitch control, external signal control and communication control
» <b>External control:</b>	--	Start/stop, direction and speed control (4-20mA, 0-5V, 0-10V, 0-10kHz external control module optional)	Start/stop control, direction control: voltage level signal or switch signal (dry contact)
» <b>Communication interface:</b>	--	RS485. Longer or Modbus protocol	USB or RS485(RJ11). Modbus protocol
» <b>Power-off memory:</b>	Return to previous state when power on	Operating parameters will be saved automatically	Pump can start running at desired time
» <b>Prime:</b>	Fast filling or emptying at full speed		
» <b>Power supply:</b>	AC 100-240V, 50/60Hz		AC 220V ± 20% / AC 110V ± 20%, 50Hz/60Hz
» <b>Dimensions (L x W x H):</b>	197 x 110 x 91 mm	232 x 142 x 149 mm	180 x 292 x 235 mm
» <b>Weight:</b>	2.3 Kg	2.38 Kg	5.0 Kg
» <b>Power consumption:</b>	15W	25W	50W
» <b>Operating temperature:</b>	0 to 40 °C		
» <b>Relative humidity:</b>	< 80%		
» <b>IP rate:</b>	IP31		

Other options (with different channels, precision, flow rate...) are available on demand depending on the specific requirements.



 [more info](#)

## 2.1.2. Single & Dual Syringe Pumps LP series

Syringe pumps LP offer a suitable solution for high accuracy and small flow rate liquid transferring.

References	LSP01-3A	LSP01-2A	TJ-3A / W0109-1B	LSP02-2B		
<b>Syringe pump specifications</b>	 <b>CE</b>	 <b>CE</b>	 <b>CE</b>			
» <b>Working Mode:</b>	Infusion		Infusion, withdrawal, infusion/withdrawal, withdrawal/infusion, continuous			
» <b>Channels:</b>		1		2		
» <b>Pump stroke:</b>	140 mm	90 mm		140 mm		
» <b>Advance per microstep:</b>	0.156 µm	0.031 µm	0.165 µm	0.156 µm		
» <b>Max. linear rate:</b>	65 mm/min	13 mm/min	79.4 mm/min	130 mm/min		
» <b>Min. linear rate:</b>	5 µm/min	1 µm/min	7.94 µm/min	5 µm/min		
» <b>Linear force:</b>	> 90 N		> 180 N			
» <b>Accuracy:</b>	$\leq \pm 0.5\%$ error in the condition of > 30% of max. infusion distance					
» <b>Flow rate:</b>	0.83 nL/min – 54.2 mL/min	0.16 nL/min – 10.8 mL/min	0.139 µL/min – 52.9 mL/min	0.83 nL/min – 150.5 mL/min		
» <b>Syringe size:</b>	10 µL – 60 mL		1 – 60 mL			
» <b>Display setting:</b>	Display volume, flow rate or linear speed (128x64 graphic LCD)					
» <b>Power-off memory:</b>	Storing the running parameters automatically					
» <b>State signal output:</b>	2 output signals (OC gate signal) to indicate start/stop and direction					
» <b>Control signal input:</b>	Falling edge or TLL signal to control start/stop					
» <b>Comm. interface:</b>	RS485					
» <b>Power supply:</b>	AC 90V-260V / 15W		AC 90V-260V / 10W	AC 90V-260V / 20W		
» <b>Operating temperature:</b>	0 to 40 °C					
» <b>Relative humidity:</b>	< 80%					
» <b>Dimensions (D X W X H):</b>	280 x 210 x 140 mm	170 x 108 x 70 mm / 245 x 100 x 95 mm (controller / drive unit)	280 x 250 x 140 mm			
» <b>Weight:</b>	3.6 Kg	0.8 Kg (controller) 1.3 Kg (drive unit)	4.3 Kg			

Other options (with different channels, precision, flow rate...) are available on demand depending on the specific requirements.



 **more info**

References	dLSP510	dLSP520	dLSP510 Pro	dLSP520 Pro
<b>Syringe pump specifications</b>				
» <b>Working Mode:</b>	Infusion, withdrawal, infusion/withdrawal, withdrawal/ infusion, auto repeated, programming (on dedicated PC software)			
» <b>Channels:</b>	1	2	1	2
» <b>Advance per microstep:</b>	0.03255 $\mu\text{m}/\mu\text{step}$		0.015625 $\mu\text{m}/\mu\text{step}$	
» <b>Linear speed:</b>	0.0833 $\mu\text{m}/\text{min}$ – 180 mm/min		0.04 $\mu\text{m}/\text{min}$ - 86.4 mm/min	
» <b>Step speed:</b>	23.4375 sec/ $\mu\text{step}$ - 10.85 $\mu\text{sec}/\mu\text{step}$			
» <b>Flow rate:</b>	0.0007 nL/min – 120.044 mL/min		0.0003 nL/min – 57.621 mL/min	
» <b>Linear travel accuracy</b>	$\pm 0.5\%$		$\pm 0.35\%$	
» <b>Linear travel CV:</b>	$\pm 0.05\%$			
» <b>Linear force:</b>	40lbs/18kg @ 100% force selection			
» <b>Motor and drive:</b>	1.8° step motor with 1/64 microstepping			
» <b>Syringe size:</b>	0.5 $\mu\text{L}$ – 60 mL	0.5 $\mu\text{L}$ – 30 mL	0.5 $\mu\text{L}$ – 60 mL	0.5 $\mu\text{L}$ – 30 mL
» <b>Display:</b>	7inch, 1024x600, IPS HD LCD			
» <b>Control mode:</b>	Touch screen control, dedicated PC or Android App control, footswitch control, RS485 communication control			
» <b>Calibration:</b>	Improve flow rate/ dispensing volume precision and accuracy			
» <b>Voice reminder:</b>	N/A		For working progress, alarm, diagnosis	
» <b>Intelligent diagnosis:</b>	N/A		For presence of syringes, syringe leakage	
» <b>Screen lock:</b>	To prevent misoperation			
» <b>Electronic signature:</b>	N/A		Meet the requirement of 21CFR Part 11	
» <b>Support 3Q (IQ/OQ/PQ):</b>	Meet GMP requirement			
» <b>EMC:</b>	CE (TUV) certified			
» <b>Dimensions (D X W X H):</b>	Drive unit: 260mm x185mm x 180mm, Controller: 190mm x123mm x 33mm			
» <b>Power supply:</b>	AC 100V-240V/30W 50/60Hz		AC 100V-240V/20W 50/60Hz	
» <b>Operating condition</b>	Temperature: 5°C - 40°C, Relative humidity<85%			
» <b>IP rating:</b>	IP31			
» <b>Weight:</b>	Drive unit: 3.49kg, Controller: 0.37kg			

Other options (with different channels, precision, flow rate...) are available on demand depending on the specific requirements.



 [more info](#)

## 2.1.3. Single & Multi Syringe Pumps NE series

Syringe pumps NE provide a very affordable solution for fluids handling in multiple applications.

References	NE-300	NE-1000	NE-4000	NE-1600/1800/1200
<b>Syringe pump specifications</b>	 CE	 CE	 CE	
» <b>Working Mode:</b>	Infusion		infusion/withdrawal	
» <b>Channels:</b>	1	2		Up to 12
» <b>Motor type:</b>		Step motor		
» <b>Motor step per resolution:</b>	400		200	
» <b>Microstepping:</b>		1/8 to 1/2 depending on motor speed		
» <b>Advance per step:</b>	0.2126 µm to 0.8504 µm depending on motor speed	0.4252 µm to 1.7009 µm depending on motor speed	0.1323 µm to 0.5292 µm depending on motor speed	
» <b>Maximum speed:</b>	38 mm/min	51 mm/min	184 mm/min	35 mm/min
» <b>Minimum speed:</b>	0.7 µm/min	1.3 µm/min	0.4 µm/min	
» <b>Linear force:</b>	> 150 N at minimum speed, 80 N at maximum speed	> 400 N at minimum speed, 80 N at maximum speed	> 700 N at minimum speed, 130 N at maximum speed	
» <b>Accuracy:</b>	Within +/- 1% over length of syringe, exclusive of syringe variations			
» <b>Flow rate:</b>	12 nL/min – 20 mL/min	12 nL/min – 30 mL/min	25 µL/min – 100 mL/min	8 nL/min – 20 mL/min
» <b>Syringe size:</b>	1 – 60 mL (140 mL partially filled)			0.5 µL – 140 mL
» <b>Number of program phases:</b>	--	41		
» <b>Comm. interface:</b>	--	RS-232 (network up to 100 pumps)		
» <b>Power supply:</b>	Unregulated linear external wall adapter, country and power source specific (or compatible regulated power supply)			
» <b>Dimensions (D X W X H):</b>	229 x 146 x 114 mm		260 x 381 x 127 mm	
» <b>Weight:</b>	1.63 Kg		4.6 Kg	

Other options (with different channels, precision, flow rate...) are available on demand depending on the specific requirements.

Accessories, such as syringes, cables, control software, etc..., are also available.

**Note:** Specifications subject to change without prior notice. *Not for Clinical Use on Humans.*



 [more info](#)

## 2.1.4. Microfluidic & High-pressure Syringe Pumps NE series

Syringe pumps NE series also offer solutions for microfluidic and high-pressure applications.

References	NE-1002X	NE-4002X	NE-8000
<b>Syringe pump specifications</b>	 CE	 CE	 CE
» <b>Working Mode:</b>	Infusion / withdrawal		
» <b>Channels:</b>	1	2	1
» <b>Motor type:</b>	Step motor		
» <b>Motor step per resolution:</b>	400	200	
» <b>Microstepping:</b>	1/16 to 1/2 depending on motor speed	1/8 to 1/2 depending on motor speed	1/8 to 1/1 depending on motor speed
» <b>Advance per step:</b>	4.2522 nm to 34.0179 nm depending on motor speed	0.4252 µm to 1.7009 µm depending on motor speed	0.5051 µm to 4.0409 µm depending on motor speed
» <b>Maximum speed:</b>	2.245 mm/min	183.369 mm/min	300.33 mm/min
» <b>Minimum speed:</b>	0.014 µm/min	1.402 µm/min	1.665 µm/min
» <b>Linear force:</b>	> 650 N at minimum speed, 80 N at maximum speed	> 400 N at minimum speed, 80 N at maximum speed	> 850 N at minimum speed, 445 N at maximum speed
» <b>Accuracy:</b>	Within +/- 1% over length of syringe, exclusive of syringe variations		
» <b>Flow rate:</b>	0.008 nL/h – 1246 µL/min	0.008 nL/h – 1555 µL/min	1.726 µL/h – 247.4 mL/min
» <b>Syringe size:</b>	0.5 µL – 60 mL (140 mL partially filled)		0.5 µL – 140 mL (200 mL partially filled)
» <b>Number of program phases:</b>	41		
» <b>Comm. interface:</b>	RS-232 (network up to 100 pumps)		
» <b>Power supply:</b>	Unregulated linear external wall adapter, country and power source specific (or compatible regulated power supply)		
» <b>Dimensions (D X W X H):</b>	229 x 146 x 114 mm		286 x 156 x 162 mm
» <b>Weight:</b>	1.63 Kg		3.55 Kg

Other options (with different channels, precision, flow rate...) are available on demand depending on the specific requirements.

Accessories, such as syringes, cables, control software, etc..., are also available.

**Note:** Specifications subject to change without prior notice. **Not for Clinical Use on Humans.**



 [more info](#)

## 2.2. FLOW SYSTEM PACKS

MicruX provides different accessories usually required for using the standard thin/thick-film (micro)electrodes in flowing liquids systems. Thus, MicruX has available different packs of accessories for using thin/thick-film electrodes in flow system with the **All-in-One platform (Flow-cell add-on)**.

### 2.2.1. Basic fitting pack (Ref. B-PACK)

Part reference	Items	Amount
	008NF16-2100 Fitting nuts (1/4" - 28 UNF - 1/16" OD tubing)	1 pk (5 units)
	008FT16-2310 Ferrules PTFE/SS (1/4" - 28 UNF - 1/16" OD tubing)	1 pk (5 units)
	008T16-080-1 PTFE tubing (OD: 1,6mm - 1/16" - ID: 0,8 mm)	1 m
	LSPS10 Luer-slip plastic syringes (10 mL)	5 units
	DS001 Disposable scalpel	1 unit

### 2.2.2. Basic-Plus pack (Ref. B-PACK+)

Part reference	Items	Amount
	008NF16-2100 Fitting nuts (1/4" - 28 UNF - 1/16" OD tubing)	1 pk (5 units)
	008FT16-2310 Ferrules PTFE/SS (1/4" - 28 UNF - 1/16" OD tubing)	1 pk (5 units)
	008T16-080-1 PTFE tubing (OD: 1,6mm - 1/16" - ID: 0,8 mm)	1 m
	GL32 Glass reservoir (GL32 thread - 50 mL)	2 units
	0032T-2 Bottle cap (GL32 thread/ 2 x Luer ports)	2 units
	LSPS10 Luer-slip plastic syringes (10 mL)	5 units
	DS001 Disposable scalpel	1 unit

### 2.2.3. Full system pack (Ref. F-PACK)

Part reference	Items	Amount
	ED-AIO-CELL-1x AIO platform (Drop + Flow-cell add-on)	1 unit
	ED-TF-Electrodes Standard thin-film microelectrodes	25 units
	LP-L100-1E/DG-2(10) Peristaltic Tube Pump (two channels)	1 unit
	38-0XXX Standard peristaltic tubes (two different diameters)	10 units
	7010 / 7012 Injection valve (20 µL loop) with loop fill port	1 unit
	008NF16-2100 Fitting nuts (1/4" - 28 UNF - 1/16" OD tubing)	1 pk (5 units)
	008FT16-2310 Ferrules PTFE/SS (1/4" - 28 UNF - 1/16" OD tubing)	1 pk (5 units)
	008T16-080-1 PTFE tubing (OD: 1,6mm - 1/16" - ID: 0,8 mm)	1 m
	GL32 Glass reservoir (GL32 thread - 50 mL)	2 units
	0032T-2 Bottle cap (GL32 thread/ 2 x Luer ports)	2 units
	LSPS10 Luer-slip plastic syringes (10 mL)	5 units
	DS001 Disposable scalpel	1 unit
	TW001 Tweezers	1 unit
	SP001 Mounting brackets / panels	1 set

Other pack options; with different peristaltic or syringe pumps, additional accessories..., are also available on demand. Packs might be customized considering the specific requirements of customers.



 [more info](#)

## 2.3. DIGITAL MICROSCOPE

The Standalone Desktop LCD Digital Microscope ([ref. SDM-1200x-LCD](#)) provides a great complement for a wide range of applications including inspection of electronics, microfluidic channels, electrodes, etc...

TECHNICAL FEATURES	
	» <b>Image Sensor:</b> 5 MegaPixel (up to 12M by interpolation)
	» <b>Controller:</b> High Speed DSP
	» <b>Flicker Rate:</b> 50Hz/60Hz
	» <b>Focus Range:</b> Manual Focus From 10mm to 50mm
	» <b>Light Source:</b> 8 LEDS with Adjustable Brightness
	» <b>Digital Magnification:</b> Up to 1200x
	» <b>Optical Magnification:</b> 10x to 300x
	» <b>Battery:</b> Rechargeable 3.7V/1050 mAh Li-ion Battery
	» <b>Working Time:</b> 2 hours
	» <b>Charge Time:</b> 3 hours
	» <b>Video Format:</b> AVI
	» <b>Video Resolution:</b> VGA, QVGA - 30 fps
	» <b>LCD Screen:</b> 3.5" LCD screen, 4:3 ratio, resolution 320x240 pixels
	» <b>OSD Languages:</b> English, German, French, Spanish, Russian, Italian, Portuguese, Dutch, Polish, Japanese, Korean, Chinese
	» <b>microSD Card:</b> Up to 32GB microSDHC
	» <b>TV Output:</b> Available (to any monitor with TV in)
	» <b>Dimensions:</b> 22.9 x 15.2 x 15.2 cm
	» <b>Weight:</b> 0.9 Kg



The **Digital Microscope** operates completely standalone or compatible with PC, Mac and iPad (using iPad camera kit for image import). Up to **1200x magnified** and **LED illuminated** viewing, snapshot, filming and measurement calibration functions.

### » Package Contents

- » Digital Microscope
- » Quick Start Guide
- » Software CD



- » Battery
- » USB cable
- » TV cable



- » Calibration chart
- » Cleaning fabric
- » microSD card

## 2.4. OTHER ACCESSORIES

MicruX provides any additional complementary tools necessary to suitable work with microfluidic devices, electrochemical sensors and portable analytical instrumentation.

### » Bipotentiostat cable – miniUSB plug

#### » Ref. ECSTAT-USB



Bipotentiostat cable with **miniUSB plug** for using in combination with **MicruX® ECStat** to directly connect the MicruX' electrochemical platforms with thin-film electrodes.

*Cable dimensions: 50 cm long*

### » Bipotentiostat cable – Banana plug

#### » Ref. ECSTAT-CAB2M




Bipotentiostat cable with **2-mm male banana plug** (+ alligator clips) for using in combination with **MicruX® ECStat** to connect the electrodes of detection system.

*Cable dimensions: 100 cm long*

### » ECsens cable adaptor – Banana plug

#### » Ref. ECSENS-CAB2M



Cable adaptor with **2-mm male banana plug** (+ alligator clips) for using in combination with **MicruX® ECsens** to connect any kind of electrodes with this miniature potentiostat.

*Cable dimensions: 50 cm long*

# PAIXÃO **pela** **CIÊNCIA**

compre online! 



16 3374.5031  
[central@scqonline.com](mailto:central@scqonline.com)  
[scqonline.com](http://scqonline.com)

